

CC Aluminum All Welded Enclosed Cabinets

ITEM # _____
MODEL # _____ QTY _____
PROJECT _____

- All Aluminum Construction with Stainless Hardware
- Designed for 18" x 26" Trays
- Available in 1" or 1.5" Shelf Spacing Configurations
- Full & Half Size Mobile Units on 5" Poly-U Casters
- Fully Welded Assembly for Strength
- Door Swings 270 degrees with Stainless Steel Gravity Latch
- Custom Sizes Available



CC40

For CEC's complete product menu, visit www.choiceequipmentcompany.com or call 706.693.2484



Specifications

Construction

Constructed of Heavy-Duty extruded 6063 aluminum alloy.

Frame

Uprights are 2.5" x 1" channel. Door, and base are 1/8" solid aluminum. Top and rear panel are constructed from .090 solid aluminum. Cross brace is 3/4" square aluminum tubing. Side ledge panels are tongue and groove with 1" or 1.5" spacing.

Casters

Heavy Duty 5" Poly-U Casters on all units for easy maneuverability.

Model Number	Overall Dimensions						Pan Capacity (18x26)	Approx Ship Wt	
	Length		Depth		Height			lb	kg
	in	mm	in	mm	in	mm			
End Load, 1.5" Spacing									
CC16	23	584	28	711	32	813	16	82	37
CC24	23	584	28	711	44	1118	24	90	41
CC32	23	584	28	711	56	1422	32	98	44
CC40	23	584	28	711	70	1778	40	108	49
End Load, 1" Spacing									
CC60	23	584	28	711	70	1778	60	115	52



CC16

Enclosed Cabinet Options

- BK Wheel Brakes
- B Corner Bumpers
- CB Continuous Bumpers
- ODL Open Door Lock

Option codes are a suffix to part numbers preceded by a hyphen.

For example, the model number for a CC16 16 tray rack with brakes and continuous bumpers would be: CC16-BK-B

For CEC's complete product menu, visit www.choiceequipmentcompany.com or call 706.693.2484

