

CCSR Aluminum All Welded Speed Rack Cabinets

- All Aluminum Construction
- Solid Top and Solid Base
- Open Front and Rear
- Designed for 18" x 26" Trays
- Available in 1" or 1.5" Shelf Spacing Configurations
- Full Size & Half Size Mobile Units on 5" Poly-U Casters
- Fully Welded Assembly for Strength
- Custom Sizes Available

ITEM # _____
MODEL # _____ QTY _____
PROJECT _____



CCSR40

For CEC's complete product menu,
visit www.choiceequipmentcompany.com
or call 706.693.2484



Specifications

Construction

Constructed of Heavy-Duty extruded 6063 aluminum alloy.

Frame

Uprights are 2.5" x 1" channel. Base is 1/8" solid aluminum. Top is constructed from .090 solid aluminum. Cross brace is 3/4" aluminum rod. Side ledge panels are tongue and groove with 1" or 1.5" spacing.

Casters

Heavy Duty 5" Poly-U Casters on all units for easy maneuverability.

| Model Number | Overall Dimensions | | | | | | Pan Capacity (18x26) | Approx Ship Wt | |
|-------------------------------|--------------------|-----|-------|-----|--------|------|-------------------------|----------------|----|
| | Length | | Depth | | Height | | | lb | kg |
| | in | mm | in | mm | in | mm | | | |
| End Load, 1.5" Spacing | | | | | | | | | |
| CCSR16 | 23 | 584 | 28 | 711 | 32 | 813 | 16 | 68 | 31 |
| CCSR32 | 23 | 584 | 28 | 711 | 56 | 1422 | 32 | 78 | 35 |
| CCSR40 | 23 | 584 | 28 | 711 | 70 | 1778 | 40 | 88 | 40 |
| End Load, 1" Spacing | | | | | | | | | |
| CCSR60 | 23 | 584 | 28 | 711 | 70 | 1778 | 60 | 95 | 43 |



CCSR16

Speed Rack Cabinet Options

- BK Wheel Brakes
- B Corner Bumpers
- CB Continuous Bumpers

Option codes are a suffix to part numbers preceded by a hyphen.

For example, the model number for a CCSR16 16 tray rack with brakes and corner bumpers would be: CCSR16-BK-B

For CEC's complete product menu, visit www.choiceequipmentcompany.com or call 706.693.2484

