PR 25 Aluminum All Welded Oval Tray Racks

ITEM #	
MODEL #	QTY
PROJECT	

- All Aluminum Construction
- Compatible with 18" x 26" trays, 12" x 20" steam table trays, and up to 23" oval trays
- Available in 10, 12, 15, 18, and 20 tray capacities
- High Quality 5" Polyurethane swivel casters for easy maneuvering
- Fully welded frame for strength



PR25-A-2310

For CEC's complete product menu, visit www.choiceequipmentcompany.com or call 706.693.2484



Specifications

Construction

Constructed of Heavy-Duty extruded 6063 aluminum alloy.

Casters

Units feature a High Quality 5" Polyurethane with full thread guard swivel casters.

Uprights & Cross Braces

All welded 1-1/8" square tubular frame with rounded-edges.

Runners

Tray runners are all aluminum and fully welded to the frame. Each runner angle measures 2" x 6.375" x .090 thick.

	Overall Dimensions							Dunney Chaoing		Annuay Chin Wa	
Model Number	Width		Length		Height		Pan Cap	Runner Spacing		Approx Ship Wt	
	in	mm	in	mm	in	mm	-	in	mm	lb	kg
PR25-A-2310	26	660	26	660	69	1753	10	6	152	80	36
PR25-A-2312	26	660	26	660	69	1753	12	5	127	84	38
PR25-A-2315	26	660	26	660	69	1753	15	4	102	92	42
PR25-A-2318/65	26	660	26	660	64	1626	18	3	76	103	47
PR25-A-2320	26	660	26	660	69	1753	20	3	76	105	48

Pan Rack Options: (all welded units only)

520U 5x2 Poly-U Caster Upgrade

BK Locking Brakes (2) VB Vertical Bumpers

B Corner Bumpers (w/ plate casters or solid base)

SB Solid Base

SBCB Solid Base w/ full perimeter bumper TGA Tray Guard for Aluminum Racks

AT Aluminum Top

Pan Rack option codes are a suffix to part numbers preceded by a hyphen.

For example, the model number for a PR25 15 tray rack with locking brakes and a solid base would be:

PR25-A-2315-BK-SB

Custom options are available. Please contact our factory for more details.

For CEC's complete product menu, visit <u>www.choiceequipmentcompany.com</u> or call 706.693.2484

