

PR22 – *HEAVY DUTY* ALUMINUM UNIVERSAL ANGLE PAN RACK







frame with 1" cross braces, a rounded-edges

HD Runners

Runner angles measure 1-1/4" x 3-1/4" x .090" thick



HD Casters
High Quality 5" x 2" Polyurethane
swivel casters

Construction

- Constructed of Heavy-Duty extruded 6063 aluminum alloy.
- Front load 18" opening fits 18" x 26" trays and steam table pans (12" x 20")
- Side load 21" opening fits 20" x 20" Glass Racks and 2 steam table pans (12" x 20") per runner
- 3-¼" wide Universal tray slide
- Available in standard 71 inch or refrigerator 64 inch heights
- Available in 10, 11, 12, 15, 18, and 20 tray capacities
- Fully welded frame for strength

Casters

- High Quality 5" x 2" Polyurethane swivel casters
- Casters Bolted to Wheel channel

Uprights & Cross Braces

• All welded 1-1/4" square tubular frame with 1" cross braces, all rounded-edges

Runners

- Tray runners are all aluminum and fully welded to the frame
- Runner angles measure 1-1/4" x 3-1/4" x .090" thick

EXAMPLE: PR22-A-1815-BKSB (HD Universal Angle Pan Rack, Front Load [21"W x 26"D], 15 Pan Capacity [4" Runner Spacing], with Locking Brakes and a Solid Base)

| EX. break-down: PR22-A | | - | 18 | | | 15 | | | | - | BKSB | |
|--|--|----------------|---|-----|-------------|---|--------------|-------------------|--------|---|---|--|
| Heavy Duty Universal Angle Pan Rack | | | Pan Load Direction | | Width Depth | | Capacity | Runner Spacing | Height | Heav | leavy Duty Universal Angle Rack Options | |
| PR22-A | Heavy Duty Universal Angle Pan Rack | 18 | Front Load | 21" | 26" | 26" Full Size | | | | AT | Aluminum Top | |
| | | 20 | Front Load Fits 20" x 20" Glass Racks and steam table pans (12" x 20") | 23" | 26" | 10 | 10 Pan Cap. | 6" | 72" | ST | Stainless Top | |
| | | | | | | 11-64 | 11 Pan Cap.* | 5" | 64" | PT | Poly Top | |
| | | | | | | 12 | 12 Pan Cap. | 5" | 72" | 620U | Heavy Duty 6x2 Poly-U Plate Caster | |
| | | | | | | 15 | 15 Pan Cap. | 4" | 72" | BK | Locking Brakes (2) | |
| | | | | | | 18-64 | 18 Pan Cap.* | 3" | 64" | VB | Vertical Bumpers | |
| | | | | | | 20 | 20 Pan Cap. | 3" | 72" | В | Corner Bumpers (w/ plate casters or solid base) | |
| | | | | | | *64 inch height designed for refrigerator use | | | ise | SB | Solid Base | |
| | | | | | | | | | | SBCB | Solid Base w/ full perimeter bumper | |
| | | | | | | | | | | TGA | Tray Guard for Aluminum Racks | |
| | | | | | | | | | | Multiple Pan Rack Options may be selected by writing each option code subsequently without dashes or spaces. For example, if you want a Pan Rack with locking brakes and a solid base, you would write in the box below: BKSB | | |
| | Select a code | e (in B | Build Your Heav LUE) from each category and fill in t | | | | | | | Universa | al Angle-size Pan Rack | |
| | PR22-A | - | | | | | | | | - | | |
| | PR22-A | - | | | | | | | | - | | |



LIMITED WARRANTY

Choice Equipment Company, Inc. warrants to the original purchaser that all of its goods and services sold shall be free of defect in material or workmanship during the twenty-four (24) months, twelve (12) months on wheels and casters, from the date of shipment or performance, provided the product has been used within the following restrictions:

- 1. The product was used for its intended purpose.
- 2. The product was properly handled, stored, installed, maintained and operated.
- 3. The product was not loaded beyond the product's load capacity.
- 4. The product is cleaned and maintained with a cleansing agent generally accepted by the industry and the instructions of the specific agent are followed.
- 5. Any abuse or misuse of, changes to, alteration of, or improper maintenance of original equipment shall void this warranty in its entirety.

If any product provided by Choice Equipment Company, Inc. shows defect in material or workmanship, CEC will, at its option, repair or replace the defective product if (1) CEC has received notice of such defects within the specified warranty period, and (2) upon CEC's request, the defective items is returned at CEC's cost to a location designated by CEC.