

# UC110 – ALUMINUM ANGULAR FRAME DOLLY



UC110-2733

### Construction

- Constructed of Heavy-Duty 3003-H14 aluminum alloy

### Base

- Standard base is made from 1.5" x 1.5" x 3/16" Thick aluminum Angle
- Pull hook is constructed from 1/2" aluminum solid rod
- Heavy Duty (HD) Option:** features a 2" x 2" x 1/4" Aluminum angle base

### Casters

- 5" Poly-U plate casters
- Heavy Duty (HD) Option:** 5" x 2" Poly-O Plate Casters with 1/2" diameter axle and Delrin bearing, bolted on with all Stainless steel hardware

**EXAMPLE: UC110-2722-HD** (Aluminum Angular Frame Dolly, for 27" x 22" Bread Trays [27"W x 22"D x 5" H], with 5" x 2" Heavy Duty Poly-Urethane Casters)

EX. break-down: UC110		2722				HD	
Aluminum Angular Frame Dolly	For Tray Size	Width	Depth	Height	Aluminum Angular Frame Dolly Options		
UC110 Aluminum Angular Frame Dolly	1723 17" x 23" Trays	18"	24"	5"	520U	5" x 2" Heavy Duty Poly-Urethane Casters	
	2024 20" x 24" Trays	20"	24"	5"	620U	6" x 2" Heavy Duty Poly Urethane Casters	
	2618 18" x 26" Bun Pans	18"	26"	5"	COR	Tamper proof Correctional Hardware, 6" x 2" Perma-TPR Wheels Upgrade	
	2722 27" x 22" Bread Trays	27"	22"	5"	HD	Heavy Duty Construction with 5" x 2" Heavy Duty Poly-olefin Casters	
	2733 27" x 33" Bread Trays	27"	33"	5"	<i>Multiple Options may be selected by writing each option code subsequently without dashes or spaces. For example, if you want 5" x 2" Heavy Duty Poly-Urethane casters and a Heavy Duty Dolly, you would write in the box below: 520UHD</i>		
	2926 29" x 26" Bread Trays	29"	26"	5"			
	2919 29" x 19" Stack and Nest Tote	29"	19"	5"			

### Build Your Aluminum Angular Frame Dolly Part Number

Select a code (in BLUE) from each category and fill in the boxes below. Use this Part Number when you order your Aluminum Angular Frame Dolly

UC110	-		-	
UC110	-		-	

Choice Equipment Company, Inc. warrants to the original purchaser that all of its goods and services sold shall be free of defect in material or workmanship during the twenty-four (24) months, twelve (12) months on wheels and casters, from the date of shipment or performance, provided the product has been used within the following restrictions:

1. The product was used for its intended purpose.
2. The product was properly handled, stored, installed, maintained and operated.
3. The product was not loaded beyond the product's load capacity.
4. The product is cleaned and maintained with a cleansing agent generally accepted by the industry and the instructions of the specific agent are followed.
5. Any abuse or misuse of, changes to, alteration of, or improper maintenance of original equipment shall void this warranty in its entirety.

If any product provided by Choice Equipment Company, Inc. shows defect in material or workmanship, CEC will, at its option, repair or replace the defective product if (1) CEC has received notice of such defects within the specified warranty period, and (2) upon CEC's request, the defective items is returned at CEC's cost to a location designated by CEC.